

Insulated stools  
Tabourets isolants.  
Isolerende bankjes.

NBN 761 -01  
NBN 761 -02

Indoor insulated stool / Tabouret isolant intérieur / Isolerend bankje binnendienst				
REF		Height Hauteur Hoogte	Nominal voltage Tension nominale Nominale spanning	Dimensions Afmetingen
Wood /Bois /Hout	P.V.C.	(cm)	(kV)	(cm)
TIN 017		21	17,5	50x50
TIN 024		21	24	50x50
TIN 045		28,5	40	50x50
TIN 060		34	60	50x50
	TIN 017 Pla *	26	17,5	50x50
	TIN 024 Pla	26	24	50x50
	TIN 030 Pla *	26	30	50x50
	TIN 045 Pla	31	40	50x50
	TIN 060 Pla	34	63	50x50

(\*) = Stock



TIN 017



TIN 017 PLA



TIN 030 PLA



TEX 024



TEX 045 PLA

Outdoor insulated stool / Tabouret isolant extérieur / Isolerend bankje buitendienst					
REF		Height Hauteur Hoogte	Nominal voltage Tension nominale Nominale spanning	Sheds Jupes Schijven	Dimensions Afmetingen
Wood /Bois /Hout	P.V.C.	(cm)	(kV)	N°	(cm)
TEX 017 *		34	17,5	2	50x50
TEX 024		34	24	2	50x50
TEX 045		44	45	3	50x50
TEX 060		49	60	3	50x50
	TEX 017 P	35	17,5	2	52x52
	TEX 024 P	35	24	2	52x52
	TEX 045 P	43,5	45	3	52x52
	TEX 060 P	51,5	63	4	52x52

(\*) = Stock

Insulated panel up to 51 kV  
Panneau isolant jusqu'à 51 kV  
Isolerend paneel tot 51 kV

IEC 243-1  
Oil Tested

REF.	Dimensions / Afmetingen (mm)	Voltage
Witta 1001	2500 x 1000 x 10	51 kV
Witta 1002	2500 x 1250 x 10	51 kV
Witta 1003	2000 x 1250 x 10	51 kV
Witta 1004	2000 x 1000 x 10	51 kV
Witta 1005	3000 x 1000 x 10	51 kV
Witta 1006	3000 x 1250 x 10	51 kV



Delivered with protection film.  
Livré en film protecteur.  
Geleverd in beschermende folie.