

Digital ground/earth resistance tester.
Mesureur de résistance de terre digital.
Digitale aardingsweerstandsmeter.

- Simple, fully automatic operation
- 3 or 4 terminal measurement
- Autoranging
- Noise rejection to 40 V
- Water resistant case for outdoor use.
- Digital LCD display
- Simple, opération automatique
- Commutation 3 ou 4 fils.
- Commutation automatique
- Bruit parasite admissible jusqu'à 40 V.
- Boîtier étanche, utilisation extérieur.
- Affichage digital LCD.
- Eenvoudig, volledig automatisch
- 3 of 4 draadaansluiting
- Autorangering
- Ruisonderdrukking tot 40 V.
- Waterbestendig voor buitengebruik.
- Digitale LCD scherm.

Art.	DET 6/2 D	DET 5/4 D	DET 5/4 R (type EDF)
commutation 3 ou 4 fils	3-terminal measurement		3 or 4 terminal measurement
Weight / Poids / Gewicht	0,82 kg		1,27 kg
Powered / Alim. / Voeding	Batteries / Piles / Batterijen 6 x 1,5 V (AA) LR6		Internal rechargeable battery. Accu. rechargeable intégré. Oplaadbare interne accu.
Includes accessories / inclus	Terminal shorting bars Operating instructions	Terminal shorting bars (2) Operating instructions	
Display / écran / scherm	3-1/2 digit LCD		
Earth Resistance ranges (Autoranging) Etendues de mesure (gammes automatiques)	200 Ω Range : 0,1 Ω to 199,9 Ω 2 kΩ Range : 0,001 kΩ to 1,999 kΩ	20 Ω Range : 0,01 Ω to 19,99 Ω 200 Ω Range : 0,1 Ω to 199,9 Ω 2 kΩ Range : 1 Ω to 1,999 kΩ 20 kΩ Range : 10 Ω to 19,99 kΩ	
Accuracy (at 23°C) Précision (à 23 °C) Nauwkeurigheid (bij 23°C)	±2 % of reading ±3 digits Maximum service error ±5% of reading ±3 digits.		
Test frequency Fréquence de mesure	128 Hz ± 0,5 Hz		
Test Voltage	Max. 50 V peak		
Test current Courant de mesure Meetstroom	200 Ω Range : 1 mA a.c. r.m.s. 2 kΩ Range : 100 µA a.c. r.m.s.	20 Ω Range : 10 mA a.c. r.m.s. 200 Ω Range : 1 mA a.c. r.m.s. 2 kΩ, 20 kΩ Range : 100 µA a.c. r.m.s.	
Max. current loop resistance	An additional error of typically 1% may be introduced for current loop resistances of : 20 Ω Range : 4 kΩ 2 kΩ Range : 40 kΩ	An additional error of typically 1% may be introduced for current loop resistances of : 20 Ω Range : 4 kΩ 200 Ω Range : 40 kΩ 2 kΩ, 20 kΩ Range : 400 kΩ	
Conform / Conforme	NFC15-100, CEI 364, VDE 0413-p7, BS 7430, BS 7671, BS 6651, CEI 1010		



DET 6/2 D



DET 5/4D



DET 5/4 R



6210-161

Art	Description	Description	Beschrijving
6420-103	Carrying case	Sacoche de transport	Draagtas
6220-537	Carrying harness	Harnais de portage	Holster met draagriemen
6210-160	Carrying bag Containing : 2 galvanised steel spikes 3 cablewinder (3,15,30 m)	Sacoche contenant : 2 piquets acier galva. 3 bobinots (3,15,30 m)	Tas bevattend : 2 paaltjes galv. staal. 3 windels (3,15,30m)
6210-161	Carrying bag containing : 4 galvanised steel spikes 4 cablewinder (3,15,30,50 m)	Sacoche contenant : 4 piquets acier galva. 4 bobinots (3,15,30,50 m)	Tas bevattend : 4 paaltjes galv. staal. 4 windels (3,15,30,50 m)
6310-755	Carrying bag containing : 4 spikes, 2 spike extractors, hammer, 3 cablewinders (2 x 3,30,50m), connection & clips	sacoche contenant : 4 piquets, 2 extracteurs, marteau, 3 bobinots (2x 3,30 et 50 m), connections & pinces	Tas bevattend : 4 paaltjes, 2 extractors, 3 windels (2x3, 30, 50m), connectoren en klemmen.
6121-119	Reel of cable, 50m	1 bobinots de 50m	1 windel van 50 m
Kit R Plus	Carrying bag containing : 4 spikes, 4 winders (1x100m, 3x50m), 1 wire 2m, + terminals and connections-joints	sacoche contenant : 4 piquets, 4 tourets (1x100m,3x50m), 1 fils de 2 m avec cosses et 2 serre-joints	Draagtas bevattend : 4 paaltjes, 4 windels (1x100m,3x50m) 1 draad 2m, kabelschoen en joints



Kit R Plus