

ESD G2 - Conductive Smooth Rubber

- **Heat, chemical, and abrasian resistant.**
Excellent floor mat for around wave solder machines and other challenging manufacturing environments.
- **Easy to cut.**
Configure to fit your requirements.
- **Durable homogeneous rubber.**
Will never delaminate.
- **reversible rubber.**
Extended use, saves money.
- **10³ - 10⁵ ohm resistance.**
Meets ESD protective flooring requirements of IEC 61340-5-1.
- **100% Premium Nitrile Butadiene Rubber.**
Better value, prevents discolouring.
- **Durable industrial grade rubber.**
Excellent value providing long-lasting, good-looking life; consistent electrical properties; will never delaminate.
- **Superior heat, chemical, and wear resistance.**
Excellent choice in soldering and other challenging manufacturing environments.
- **Antistatic, low tribocharging.**
Minimal charge generation on mat.
- **High quality material with conductive electrical properties.**
When properly grounded, safely removes electrostatic charges from equipment and people to protect your ESD sensitive products.
- **Non-humidity dependence.**
Provides consistent electrical performance regardless of ambient humidity.
- **Dimensionally stable.**
Minimal shrinkage and curling.
- **Superior Quality**
- **Rp / Rg :**
10³ - 10⁵ Ohms
- **Thickness:**
1.5mm

MATS	
Art.	Description
ESD 80109	1.2m x 2.4m mat, black

ROLLS	
Art.	Description
ESD 80113	1.2m x 12.2m roll, black

