

Adjustable Elastic Wristband with Cam-Lock

- **Designed to satisfy Wrist Strap requirements of IEC 61340-5**
- **Elasticated woven fabric.**
Improved fabric.
- **Cam-lock adjustment.**
Only one item to stock; snug fit.
- **Per EN 61340-5-1 paragraph 5.5 EPA working practices**
“The primary means of grounding personnel shall normally be by a wrist strap connected to an EBP.” Paragraph 5.2.7 “The wrist strap shall consist of a band that fits snugly around the wrist and a cord to connect the band to an EBP. The wrist strap shall incorporate a quick release connection. The cord shall have a termination compatible with the EBP and shall incorporate at least one insulated current-limiting resistor. The total resistance from hand to EBP shall be in accordance with table 1 [Rg 7,5 x 10⁵ to 3,5 x 10⁷ ohms].”



Art.	Description
ESD 60064	10 mm stud version, non-allergenic
ESD 60063	4 mm stud version, non-allergenic
ESD 60061	10 mm stud version
ESD 60062	4 mm stud version

Adjustable Elastic Wristband

- **Elasticated woven fabric.**
Improved fabric.
- **Adjustable.**
Only one item to stock; snug fit.
- **Designed to satisfy Wrist Strap requirements of IEC 61340-5**
- **Per EN 61340-5-1 paragraph 5.5 EPA working practices**
“The primary means of grounding personnel shall normally be by a wrist strap connected to an EBP.” Paragraph 5.2.7 “The wrist strap shall consist of a band that fits snugly around the wrist and a cord to connect the band to an EBP. The wrist strap shall incorporate a quick release connection. The cord shall have a termination compatible with the EBP and shall incorporate at least one insulated current-limiting resistor. The total resistance from hand to EBP shall be in accordance with table 1 [Rg 7,5 x 10⁵ to 3,5 x 10⁷ ohms].”



Art.	Description
ESD 60089	4 mm stud version