

Jewel Elastic Adjustable Wrist Straps

- **High visibility.**
Bright blue, red and amber colours allow supervisor to see that worker is wearing wrist strap.
- **Rapid retraction strength polyurethane.**
High memory, less dragging on work surface, reduces tangling.
- **Superior strain relief tests in excess of 27,500,000 cycles, per Bending Life Test (exceeds by over 1,700 times the minimum requirement).**
Eliminates intermittent failures that can occur with less durable single and dual wire cords.
- **Improved snap design.**
Stronger strain relief and snap retention for long life and reliable circuit connections. Low profile keeps cord from being disconnected.
- **Superior banana plugs with patented supported spring contour.**
Fits into all standard jacks $\geq 0.398\text{cm}$ ID. Greater retention force; cords won't pull out.
- **Spring loaded 4mm or 10mm stainless steel constant contact snap.**
Provides constant electrical contact.
- **Tensile strength at each end in excess of 13.6 kg (approximately 136 Newtons).**
Longer lasting cord saves money.
- **One megohm series resistor at wrist end.**
To protect operator from accidental contact with equipment line voltage. Fulfills Paragraph 5.1.1 of IEC 61340-5-2
- **Premium coil cords designed and manufactured at our Chino, CA, USA factory.**
Made in America under our control, ensuring consistent top quality.
- **UL listed.**
Assured safety and integrity.
- **Date coded.**
Lot traceability.
- **Designed to satisfy Wrist Cord requirements of IEC 61340-5**

Coulour	Termination	Length	Resistor	Socket Size	
				4mm	10mm
Sapphire	banana	1,8 m	1 x 1	ESD 60260	ESD 60261
Ruby	banana	1,8 m	1 x 1	ESD 60262	ESD 60263
Topaz	banana	1,8 m	1 x 1	ESD 60264	ESD 60265
Emerald	banana	1,8 m	1 x 1	ESD 60266	ESD 60267
Amethyst	banana	1,8 m	1 x 1	ESD 60268	ESD 60269

