

## Three Layer Non-Marking Foot Grounder

- **Designed to satisfy Footwear requirements of IEC 61340-5.**
- **No exposed carbon.**  
Ideal for cleanrooms.
- **Non-marking interior and exterior dissipative rubber.**  
Will not mark shoes or floors - reduces maintenance costs of touching up floors.
- **Hook and stretch loop fastening assembly.**  
Genuine «non-selvedged» Velcro material - adjustable and comfortable.
- **76 cm long, 8 strand nylon polyester grounding tab.**  
Does not particulate; superior body to ground contact.
- **Reversible static dissipative 3-layer rubber.**  
Extended life expectancy; exceptional wear resistance, able to use all four wearing surfaces.
- **Bright yellow rubber cup.**  
High visibility to ensure programme compliance.
- **Rg:  $10^6$  -  $10^7$  Ohms.**



Art.	Description
ESD 70007	Heel grounder, 1 meg resistor

## Toe Grounder

- **Designed to satisfy Footwear requirements of IEC 61340-5.**
- **Wear resistant rubber.**  
Provides contact area to floor.
- **Non-marking interior.**  
Will not mark shoes.
- **Snap-loc fastening assembly.**  
Genuine «non-selvedged» Velcro material - adjustable and comfortable.
- **30 cm long, 8 strand nylon polyester grounding tab.**  
Does not particulate; superior body to ground contact.
- **Rg:  $10^6$  -  $10^7$  Ohms.**



Art.	Description
ESD 70031	Toe grounder, 1 meg resistor