

Insulating stools (dismountable feet)
Tabourets isolants (pieds dévissable)
Isolerende bankjes (uitschroefbare poten)

Conform to :
NBN 761.01
NBN 761.02

The insulating stool is used to insulate the user from the floor (from earth).

Le tabouret isolant a pour but d'isoler l'utilisateur du sol (de la terre)

Een Isolerend bankje dat dient als isolatie tussen de gebruiker en de vloer (aarde).



TIN 017 PLA

TIN 030 PLA

TIN 045 PLA

TIN 060 PLA

Indoor insulated stool
Tabouret isolant intérieur
Isolerend bankje binnen

Art.	Description	Nominal voltage Tension nominale Nominale spanning	Height Hauteur Hoogte	Size Dim. Afm.	Weight Poids Gewicht
P.V.C.		(kV)	(cm)	(cm)	(kg)
TIN 017 Pla *	NBN 761.01 **	17,5	26	50x50	2,85 kg
TIN 030 Pla *	on platform : «30 kV»	30	26	50x50	2,85 kg
TIN 045 Pla *	on platform : «45 kV»	45	31	50x50	3;25 kg
TIN 060 Pla *	-	60	51	50x50	4,60 kg

(*) = Stock

(**) Article TIN 017 PLA conform to NBN 761.01 :

With bilingual marking (French and Dutch)

Avec marquage bilingue (Fr et NI)

Met tweetalige markering (Frans en Nederlands)

Marking : **17,5 kV BINAME VOOR BINNENDIENST POUR INTERIEUR**



TEX 030 P



TEX 045 P



TEX 060 P

Outdoor insulated stool (for wet and/or rainy conditions-)
Tabouret isolant extérieur (pour conditions humide et/ou sous pluie)
Isolerend bankje buiten (voor vochtige en/of onder regenachtige omstandigheden)

Art.	Description	Nominal voltage Tension nominale Nominale spanning	Sheds Jupes Schijven	Height Hauteur Hoogte	Size Dim. Afm.	Weight Poids Gewicht
P.V.C.		(kV)	N°	(cm)	(cm)	(kg)
TEX 030 P *	on platform : «30 kV»	30	2	35	50x50	5,50 kg
TEX 045 P *	on platform : «45 kV»	45	3	43	50x50	
TEX 060 P *	-	60	4	51	50x50	

(*) = Stock